

**HAVOLINE®
SUPER 2T**

Two-Stroke Motorcycle Oil

PRODUCT CODE
3050**PACK SIZES**
20L, 4L, 1L**DESCRIPTION**

Two-stroke motorcycle oil that protects vital engine parts. It is formulated with a special low ash additive system and designed for engines requiring JASO FC or ISO EGC performance lubricants, including high output machines operating in severe service.

APPLICATIONS

- Air and liquid-cooled two-stroke motorcycle engines.
- Particularly suitable for Japanese high performance motorcycle engines.
- Latest generation, two-stroke scooter engines.
- Japanese two-stroke engines fitted to portable power equipment (other than chainsaws).
- Oil-injected engines (except marine outboard) where no fuel/oil premixing is required.
- Air-cooled, oil-gasoline premix engines at manufacturer's recommended gasoline-to-oil ratios up to 50:1.
- Two-stroke motorcycle, motor tricycle and quad-bike engines fitted with exhaust catalysts.

Not recommended for use in marine outboard engines, chainsaw engines or any CNG- or LPG-fuelled two-stroke engines.

BENEFITS**Powerful throttle response**

Power and good acceleration are maintained by providing excellent cleanliness of pistons and exhaust ports, through the reduction of ash and carbon deposits.

Reduces exhaust smoke

Superior combustion characteristics reduce smoke in exhaust emissions, which also provides improved working environment for operators of portable power equipment.

Extends engine life

Semi-synthetic base fluids provide superior lubricity to reduce wear of pistons and cylinders.

Maximises spark plug life

Low ash additive system helps to reduce ash build-up on spark plugs.

Dyed green for ease of identification.**PERFORMANCE STANDARDS**

- API TC
- JASO FC (Identification Number: 061CTC684)
(Product manufactured up to early 2011 was Identification Number: 061CTC683)
- ISO EGC
- SAE Grade (J1536) F/M 2