

SMALL ENGINE

SUPER OUTBOARD 3

Two-Stroke Marine
Outboard Motor Oil

PRODUCT CODE
2709

PACK SIZES
20L, 4L, 1L

DESCRIPTION

Premium performance, two-stroke, marine outboard motor oil formulated with a special ashless additive system. Pre-diluted with a high flashpoint, low aromatic solvent to facilitate mixing with petrol at all temperatures. Designed for engines requiring NMMA TC-W3® certified lubricants, operating in all service conditions. Dyed blue until end 2010, thereafter dyed green.

APPLICATIONS

- All water-cooled, two-stroke, marine outboard engines, including the latest designs under warranty protection.
- Oil-injected engines.
- Oil-petrol premix engines at all petrol to oil ratios up to and including 100:1.
- Air-cooled, two-stroke engines where API TD or NMMA certified oils are specified.

BENEFITS

Maintains high power output

Special blend of highly refined mineral oil and ashless additive system provides superior piston cleanliness and protection against ring sticking by minimising deposit formation, thus maintaining combustion efficiency and protecting against power loss.

Reduces maintenance costs

Special ashless additive system includes a selected synthetic component for enhanced lubricity to separate contacting surfaces with a tough lubricant film to protect against wear under high speed, peak performance conditions.

Trouble-free operation

Ashless additive system ensures that ash-induced deposits are not formed in the combustion chamber, thereby eliminating the risk of destructive pre-ignition from this source.

Maximises spark plug life

Ashless additive system reduces spark plug fouling under all operating conditions.

PERFORMANCE STANDARDS

- API TD
- NMMA TC-W3® (Certification Numbers RL-00420J).
- SAE Grade (J1536) F/M 3