HAVOLINE® MULTIGRADE

SAE 20W-50
API SG/CD Passenger Car Engine Oil

PRODUCT CODE
1459

PACK SIZES
205L, 20L, 4L, 1L

DESCRIPTION

High quality engine oil for use in older passenger car and light-duty commercial vehicle engines where API SG or lower performance lubricants are required and SAE 20W-50 viscosity is acceptable.

APPLICATIONS

- Naturally aspirated and turbocharged gasoline engines in passenger cars and light commercial vehicles.
- Four-stroke gasoline engines in portable power equipment where the manufacturer recommends conventional passenger car motor oils.

Not recommended for use in engines that require ACEA-classified oils, in turbocharged engines, in CNG or LPG-fuelled engines, in any diesel engines or in motorcycle engines.

BENEFITS

Long engine life
Proven metallo-organic anti-wear additive system resists wear by forming a protective layer on contact surfaces. Multigrade viscosity provides additional protection against wear at start-up and under high temperature operating conditions.

Preserves power and performance
Metallic detergent and ashless dispersant additive system helps to preserve power and performance by providing good control of piston and ring deposits.

Saves on maintenance
Good thermal and oxidation stability resists in-service oil degradation that contributes to filter blocking and sludge formation.

PERFORMANCE STANDARDS

- API SG/CD

Bennett's Petroleum Supplies Pty. Ltd.
ABN 71 009 508 285
Self's Point, Hobart TAS 7008 | PO Box 436, Moonah TAS 7009
T +61 3 6242 8200 | F +61 3 6228 0139 | E orders@bennettspetrol.com.au